





SCANNING-PROBE
SYSTEMS

M470.

A modular, state-of-the-art instrument
allowing users to exploit 9 local
electrochemistry techniques



M470 is the 4th generation of scanning probe systems, which includes a high-resolution scanning stage and additional probe techniques.



The M470 achieves the perfect balance of scan speed, resolution and accuracy to deliver a new standard in spatially resolved electrochemical measurements.

Outstanding performance




The fast precise closed loop positioning system is designed specifically for the demands of scanning probe electrochemistry with nanometer resolution. Combined with BioLogic's unique hybrid 32-bit DAC technology, it enables the user to select the configuration most suited to their experiments.

Advanced and flexible platform

The system is available with a combination of nine techniques which make the M470 the world's most flexible scanning probe electrochemistry platform. The M470 can be coupled to BioLogic's Premium range of potentiostats.

Wide range of options

A choice of seven modules, four different cells and a wide range of probes is offered. This is complemented by a long working distance video camera option, glove box cables, and post processing data analysis software.




AVAILABLE TECHNIQUES

- Scanning ElectroChemical Microscopy (SECM)
- Alternating current Scanning ElectroChemical Microscopy (ac-SECM)
- Intermittent contact Scanning ElectroChemical Microscopy (ic-SECM)
- Localised Electrochemical Impedance Spectroscopy (LEIS)
- Scanning Vibrating Electrode Technique (SVET)
- Scanning Droplet Cell (SDC)
- Alternating current Scanning Droplet Cell (ac-SDC)
- Scanning Kelvin Probe (SKP)
- Optical Surface Profiler (OSP)

M470 positioning system

Ultra high resolution scanning stage with an extended travel distance

The M470 scanning stage combines high resolution and a large travelling distance as well as a high speed scan.




The scanning system is based on ultra-high precision linear positioning components and offers a high resolution, coupled with a long travel distance.

The M470, with its improved reproducibility and increase in scan speed, can reduce the time taken to run samples. This lends itself to application areas where the system under study is not in a steady-state.

ic-SECM uses a piezo for fine positioning on the z-axis for topography measurement and relief. A 20-bit DAC is used for control over the piezo range, and provides position control to 0.09 nm.

M470 specifications


Workstation (all techniques)	
Scan range (x, y, z)	110 mm on all axes
Scan motor resolution	9.76 nm
Closed loop positioning	Linear zero hysteresis encoder with direct real-time readout of displacement in x, y and z
Axis resolution (x, y, z)	20 nm
Max. scan speed	10 mm/s
Measurement resolution	32-bit decoder @ up to 40 MHz
Piezo ic-SECM	
Vibration range	20 nm - 2 μ m peak to peak with 1 nm increments
Min. vibration resolution	0.12 nm calculated (16-bit DAC on 4 μ m)
Piezo crystal extension	100 μ m
Positioning resolution	0.09 nm calculated (20-bit DAC on 100 μ m)
Mechanical and electrical	
Scan head	500 x 400 x 675 mm (H x W x D)
Scan control unit	370 x 450 x 420 mm (H x W x D)
Power	250 W



Local measurement of sample conductivity and electrochemical activity with chemical selectivity

Impedance capability is included as standard for measurement without a redox mediator

Constant distance or constant height



SECM is a highly versatile technique which can be applied to a wide range of sample types regardless of conductivity. SECM has been applied to a wide variety of fields from batteries to biology.

The M470 couples to the SP-300 to perform low current, low-noise measurements simultaneously at the tip and substrate, to address specialist applications including those in surface science and the study of living cells.

The M470 includes ac-SECM as a standard experiment type. Using ac-SECM, surface phenomena can be studied without the need for a redox mediator. This feature is applicable in any field where the mediator could adversely affect the reaction under study, including corrosion.

Using the M470, either constant height or constant distance SECM can be performed. Constant distance SECM is achieved by combining SECM470 with the OSP470 or ic-SECM470 module.

Experimental data collected using the SECM470 can be imported into the modelling and analysis software package MIRA, giving access to experimental and kinetic parameters.

Typical application areas are:

Biology

- Investigate cell morphology
- Follow photosynthetic processes
- Examine the effects of toxins on biological samples

Catalysis

- High throughput screening of combinatorial libraries of catalysts

Batteries

- Understand the degradation of Li-Ion electrodes
- Investigate the distribution of materials in an electrode

Coatings & Corrosion

- Investigate the ability of smart coatings to self-heal after damage
- Determine where corrosion is occurring locally
- Follow the formation and breakdown of the passive layer

Photovoltaics

- Investigate sensitizers and electrolytes for dye sensitized solar cells

Sensors

- Study antigen binding in biosensors


SECM470/ac-SECM470 specifications

Potentiostats

Compliance voltage	±12 V
Applied potential and resolution	±10 V FSR @ 16-bit (down to 1.5 µV)
Measured potential and resolution	± 10 V FSR @ 16-bit (down to 76 µV)
Current ranges	11-decades 100 pA to 1 A
Maximum current	±500 mA
Current resolution	76 aA
Floating capability	Standard
Cell connections	2, 3, or 4 electrode
Scan rate	1 µV/s to 200 V/s
Modes	Potentiostat, Galvanostat, OCP

EIS Capability

Frequency range	10 µHz to 1 MHz
Analyser accuracy	1%, 1°
Max. frequency resolution	0.1 nHz



High resolution SECM with simultaneous topography measurement and relief


Intermittent contact SECM allows the user to measure separate topographical and electrochemical information in a single experiment.

Constant distance
ac-SECM or dc-SECM

It is well-known that classical SECM measurements are sensitive to surface activity variations as well as topographical changes, therefore it can be beneficial to perform SECM in the constant distance mode.

The solution exploits an innovative tip positioning method to perform constant distance SECM. Through ic-SECM both the surface topography and activity are resolved simultaneously and independently in a single pass experiment. The intermittent contact technique uses the standard SECM probes to follow the topography of the sample throughout the course of a scan.

Using ic-SECM470, SECM can be performed at the push of a button. The surface approach can be performed automatically allowing the M470 to approach, find, and scan the sample. The ic-SECM470 can be used in the dc or ac-SECM mode, to measure a wide range of sample types. **The ic-SECM module is offered exclusively by BioLogic** following its introduction by the University of Warwick Electrochemistry and Interfaces Group, and is protected by international patent applications.



Typical application areas are:

Batteries

- Locally compare the conductivity of solid-state electrolyte grains and grain boundaries

Coatings & Corrosion

- Image the breakdown of epoxy coatings
- Study the corrosion of welded materials
- Map hydrogen in metallic alloys

Fuel cells


- Examine the mixing of conductive particles in bipolar plates

Materials

- Investigate the electric conductivity and surface topography of boron doped diamond


ic-SECM470 specifications

Potentiostats	
Compliance voltage	±12 V
Applied potential and resolution	±10 V FSR @ 16-bit (down to 1.5 µV)
Measured potential and resolution	± 10 V FSR @ 16-bit (down to 76 µV)
Current ranges	11 decades 100 pA to 1 A
Maximum current	±500 mA
Current resolution	76 aA
Floating capability	Standard
Cell connections	2, 3, or 4 electrode
Scan rate	1 µV/s to 200 V/s
Modes	Potentiostat, Galvanostat, OCP
EIS Capability	
Frequency range	10 µHz to 1 MHz
Max. frequency resolution	0.1 nHz
Analyzer accuracy	1%, 1°
ic-SECM module	
Tip control	Piezo element and stepper
Piezo crystal extension	100 µm
Vibration frequency	80 – 600 Hz
Vibration control	20 nm – 2 µm peak to peak
Minimum increment	1 nm
Piezo drive resolution	0.095 nm
Strain gauge resolution	3.05 nm
Positioning-probe to sample surface	Autonomous



Localised impedance measurements

Measurements can be made using the powerful inbuilt sequencer to perform local frequency sweeps at set points across a surface, or map a surface switching frequencies for each map.



The principles of Localised Electrochemical Impedance Spectroscopy (LEIS) are similar to those employed in EIS, in that a small sinusoidal voltage perturbation is applied to a working electrode sample and the resulting current is measured to allow the calculation of the impedance. However, rather than measuring the bulk current, a small electrochemical probe is scanned close to the surface, measuring the localised current in the electrolyte.

Producing area maps over a sample at a single frequency has never been easier. To easily investigate changes to the sample over time the software sequencer can be used to loop LEIS area scan measurements. The LEIS470 also allows the user to make galvanic or global impedance measurements simply by choosing which mode the potentiostat is operating in, and the software does the rest.

Typical application areas are:

Batteries

- Explore the effect of surface treatments on the electrodes

Coatings


- Study the ability of smart coatings to self-heal after damage
- Investigate the occurrence of underfilm corrosion
- Follow coating failure and delamination

Corrosion

- Examine the effect of alloy composition on corrosion
- Study pit initiation of corrosion
- Investigate the corrosion resistance of metal hydrides used in hydrogen storage

LEIS470 specifications


Potentiostat	
Compliance voltage	±12 V
Applied potential and resolution	±10 V FSR @ 16-bit (down to 1.5 µV)
Measured potential and resolution	± 10 V FSR @ 16-bit (down to 76 µV)
Current ranges	11-decades 100 pA to 1 A
Maximum current	±500
Current resolution	76 aA
Floating capability	Standard
Cell connections	2, 3, or 4 electrode
Scan rate	1 µV/s to 200 V/s
EIS capability	
Frequency range	10 µHz to 3 MHz
Analyser accuracy	1%, 0.1
Max. frequency resolution	0.1 nHz



Map local electrochemical events in real time.

The Scanning Vibrating Electrode Technique (SVET) maps the electric field generated in a plane above the surface of an electrochemically active sample.

Signal extraction:
user-tuned or auto-tuned



SVET enables the user to map and quantify localised electrochemical events in real time. As a result SVET is highly applicable to corrosion studies, and is used in biology, where it is known as Vibrating Probe, to investigate extracellular currents.

The probe vibration is controlled by a piezoelectric vibration actuator allowing vibration amplitudes from 1 – 30 μm (perpendicular to the sample surface). It is an ac technique, thus, high system sensitivity can be achieved via a differential electrometer in conjunction with a lock-in amplifier.

The SVP470 vibrating probe provides increased electrical sensitivity as well as enhanced system stability.

By choosing a BioLogic potentiostat, users can access an integrated suite of dc corrosion experiments and can be used to bias the potential of the sample.

Typical application areas are:

Batteries

- Follow the effect of changing the applied potential on the activity of aqueous battery electrodes

Biology

- Follow photosynthetic processes
- Map the electric fields associated with wound healing

Coatings

- Investigate the ability of smart coatings to self-heal after damage
- Image the cathodic protection of coatings


Corrosion

- Investigate the effect of sample structure on corrosion
- Follow the electrochemical progress of corrosion in real time
- Study galvanic corrosion *in-situ* in real time

SVP470 specifications

SVP electronics


Signal chain	Phase sensitive detection using microprocessor controlled lock-in amplifier with digital dual phase oscillator and differential electrometer input
Lock-in amplifier	Software controllable gain range (1 – 10^5). Output time constant 0.01, 0.1, 1, 10 s
Differential electrometer	$10^{15} \Omega$ input impedance. Decade gain ranges 0 to 80 dB. Common mode range ± 12 V
Vibration actuator	One dimensional low voltage piezoelectric actuator
Vibration amplitude	Software set from 1 – 30 μm perpendicular to sample surface
Electrochemical sensitivity	Better than 5 $\mu\text{A}/\text{cm}^2$ (using standard PIS test approach)



Surface potential and topography measurements

Scanning Kelvin Probe (SKP) is a non-contact, non-destructive technique which is highly sensitive to changes in work function due to changes in the surface state.

Signal extraction:
user-tuned or auto-tuned



Using a vibrating capacitance probe, the SKP470 Scanning Kelvin Probe measures the work function difference between the scanned probe reference tip and sample surface. The measured work function can be directly correlated to many aspects of the surface condition, including corrosion potential.

The use of a capacitance probe allows the SKP470 to measure the sample topography. Through these topography measurements, the SKP470 can be used in height tracking mode to maintain a constant height between the probe tip and sample surface, allowing SKP measurements to be made over uneven surfaces.

Typical application areas are:

Photovoltaics

- Determine the work function of photovoltaic materials

Catalysis

- Measure changes in work function related to the effect of sample treatment on catalytic activity

Coatings & Corrosion


- Study the ability of smart coatings to self-heal after damage
- Image the breakdown of epoxy coatings
- Investigate the effect of alloy composition on corrosion
- Determine where corrosion is occurring locally

Materials

- Measure the effects of dopants on the electrical properties of a semiconductor


SKP470 specifications

SKP electronics	
Signal chain	Phase sensitive detection using microprocessor controlled lock-in amplifier with digital dual phase oscillator and differential electrometer input
Lock-in amplifier	Software controllable gain range (1 - 10 ⁵). Output time constant 0.01, 0.1, 1, 10 s Scanning specific LIA included within the M470 control unit
Differential electrometer	10 ¹⁵ Ω input impedance. Decade gain ranges 0 to 80 dB. (1x to 10000x). Common mode range ± 12 V
Vibration actuator	One dimensional low voltage piezoelectric actuator
Vibration amplitude	Software set from 0 - 30 μ m perpendicular to sample surface
Backing Potential Controller (BPC) potential range	± 10 V
BPC DAC Resolution	300 μ V
BPC sampling	0.1 Hz to 1000 Hz
BPC type	PID controller
Probe	
Probe type	Proprietary SKPR tungsten air gap. Available in 150 and 500 μ m diameter



Voltammetry and impedance measurements at the micrometric scale

Scanning Droplet Cell (SDC) shrinks the electrochemical cell to the size of a droplet to directly measure the local electrochemical characteristics of the sample of interest.



The Scanning Droplet System uses a Scanning Droplet Cell (SDC) that allows a spatially resolved, *in situ* investigation by all standard electrochemical techniques. SDC is a technique which confines a liquid in contact with a sample surface in order to measure electrochemical and corrosion reactions over a limited region where the droplet is actually in contact with the sample.

This offers the unique ability to spatially resolve electrochemical activity and to confine it exclusively to a quantifiable area of the sample.

The scanning droplet system allows the positioning of a small drop of electrolyte from the SDS head onto the sample surface. The wetted surface area under investigation acts as the working electrode and the SDS head contains the counter and reference electrodes which are electrically connected to the surface through the drop. The SDS470 is supplied with a flow type SDS, head for studies in which continuous regeneration of the droplet are key, and a small aperture reservoir head, for studies requiring increased resolution.

Typical application areas are:

Catalysis

- High throughput screening of combinatorial libraries of catalysts

Corrosion

- Probe the effect of features, like welds, on corrosion properties
- Investigate the effect of flow on corrosion
- High throughput screening of corrosion properties of alloy libraries

Materials


- High throughput screening for material discovery and optimization
- Investigate coarse grain crystalline materials

Photovoltaics

- Study the local effect of doping on donor/acceptor materials


SDS470/ac-SDS470 specifications

SDS Head	
Included SDS Heads	500 μ m PEEK, 100 μ m PEEK
500 μm Flow Head	
Type	Flow
Reference Electrode	Ag/AgCl within sensor head
Counter Electrode	Pt wire within capillary
Head Construction	PEEK with silicone rubber tubing
Aperture	ID 500 μ m, 0.196 mm ²
Resolution	< 1 mm depending on solution/surface
100 μm Reservoir Head	
Type	Reservoir
Reference Electrode	Pt wire
Counter Electrode	Pt wire
Head Construction	PEEK
Aperture	ID 100 μ m, 0.00785 mm ²
Resolution	200 μ m depending on solution/surface
Pump System	
Type	Peristaltic
Channels	2-Channels
Software control	Software control through use of experiment sequencer
Potentiostat	
Compliance voltage	± 12 V
Applied potential and resolution	± 10 V FSR @ 16-bit (down to 1.5 μ V)
Measured potential and resolution	± 10 V FSR @ 16-bit (down to 76 μ V)
Current ranges	11-decades 100 pA to 1 A
Maximum current	± 500 mA
Current resolution	76 aA
Floating capability	Standard
Cell connections	2, 3 or 4
Scan rate	1 μ V/s to 200 V/s
EIS capability	
Frequency range	10 μ Hz to 1 MHz
Analyser accuracy	1%, 1°
Max. frequency resolution	0.1 nHz



Non-contact topography measurements

Utilising a non-contact laser displacement sensor, the OSP470 module allows fast and accurate non-contact surface measurement to a very high accuracy.



Features with a step height of less than $1\text{ }\mu\text{m}$ can be imaged and measured over a height measurement range of 10 mm without touching the sample surface. The OSP470 incorporates a CCD displacement sensor mounted on the scanning head of the M470 workstation.

A tightly focused laser (650 nm) is projected onto the sample surface and the scattered light is detected by a CCD array allowing the direct displacement measurement of the diffuse scattered light. This allows a very accurate surface height profile of the entire surface to be generated and allows measurements of the surface roughness and topography features.

Most importantly, the OSP470 module will allow the use of topography data to alter the height of the probe in many of the other local electrochemistry techniques. The probe is then able to scan over uneven surfaces whilst maintaining a constant distance of the probe from the sample.

Typical application areas are:

Coatings

- Examine the morphology of polymer materials
- Study the surface roughness of aerospace coatings
- Investigate damage to coated metal surfaces

Corrosion

- Measure sample topography for height tracking corrosion investigations
- Investigate changes in topography due to corrosion attacks
- Examine topography changes due to biofilm formation

Materials

- Investigate the effects of water absorption on material swelling

Biology

- Investigate the effect of surface texture on barnacle settlement

OSP470 specifications

Sensor	
Measurement range	10 mm
Reference distance	30 mm
Maximum vertical resolution (static)	100 nm
Spot size	30 μm at focus
Scan speed	10 mm/s
Multiple readings averaged	Yes
Correct positioning	Red light/green light
Light source	650 nm class 2 semiconductor laser max. 0.95 mW
Auto-calibration for off-axis alignments	Yes
Real-time CCD readout	Yes



M470

If you need a localised view of electrochemistry, look no further than the BioLogic M470 scanning electrochemical workstation.

A fully modular instrument, the M470 can be tailored to scan 9 techniques from 7 modules. And user-friendly software means that no time will be lost learning to operate the instrument, whether you are a specialist in local electrochemistry, or new to the field.

Techniques Available

- SECM
- ic-SECM
- ac-SECM
- LEIS
- SVET
- SDC
- ac-SDC
- SKP
- OSP



Click or scan




Learn more about M470 ?
What are the benefits of this workstation ?

Scanning Product Accessories

Probes

A range of probes dedicated for use with our SECM, SVP, SKP and LEIS scanning probe applications are available for the M370 and M470 systems. SECM probes can also be used with SECM150



	Catalog n°
Fused silica-based SECM 10 µm diameter Platinum disk	U-23/10
Fused silica-based SECM 15 µm diameter Platinum disk	U-23/15
Fused silica-based SECM 25 µm diameter Platinum disk	U-23/25
Capillary based SECM 1 µm diameter Platinum disk	U-P5/1 ¹ ²
Capillary based SECM 2 µm diameter Platinum disk	U-P5/2 ¹ ²
Capillary based SECM 5 µm diameter Platinum disk	U-P5/5 ¹
Capillary based SECM 10 µm diameter Platinum disk	U-P5/10

	Catalog n°
Capillary based SECM 15 µm diameter Platinum disk	U-P5/15
Capillary based SECM 25 µm diameter Platinum disk	U-P5/25
SKP 500 µm diameter	U-SKP370/1
HR SKP 150 µm diameter	U-SKP-150
LEIS	U-LEIS370/1
SVP	U-SVP370/1

¹Unsuitable for ic-SECM/ ²Unsuitable for M370

VCAM3 Video Microscope System

The VCAM3 is a long working distance video microscope which allows users to view the positioning between probe tip and sample surface in many scanning probe electrochemistry techniques.



VCAM3 specifications

	Information
Working Distance/mm	108 mm
Min illumination/lux	0.0003
Field of view/mm	11 mm at 0.7x 1.76 mm at 4.5x
Catalog n°	U-VCAM3

Three cells are available :

The TriCell™ is a large volume, wide scan range cell, dedicated to LEIS, SVET, SKP, SDC techniques.

The μ TriCell™ and its Shallow version are dedicated to SECM techniques (dc, ac and ic mode). The Shallow μ TriCell™ contains a slightly smaller volume of electrolyte than the μ TriCell™. Furthermore, it is more accessible and ideal for ic-SECM.


The Foil Cell has been designed for use with flat, foil type samples, such as those used for battery electrodes. It has been designed to mount directly on the baseplate of the μ TriCell™ and Shallow μ TriCell™.

All TriCells accommodate samples mounted in a 32 mm diameter resin cylinder.


Cells	Volume (mL)	Catalog n°
TriCell™	700	U-TRICELL
μ TriCell™	7	U-uTRICELL
Shallow μ TriCell™	6	U-SuTRICELL
Foil Cell	1	U-uFoilCell




TriCell™



μ TriCell™



Shallow μ TriCell™



Foil Cell

M470 Glovebox Cables

The M470 Scanning Electrochemical Workstation is supplied with a full set of standard cables for use with all techniques.

For applications requiring use of the M470 in a glove box, additional cell cables are available.

These are supplied as a set of internal, feedthrough and external cables to replace a single cable.



Hermetic scan stage cable for glove box

	Electrometer	Piezo Strain Gauge	Piezo Drive	Scan Stage	3300
Content					
Feedthrough types/pins	8	6	3	8	25
Inside glove box	Electrometer cable connects directly to 8 pin LEMO feedthrough.	Cable with connector to piezo strain gauge on one side and 6-pin Jaeger connector on the other side (length 1.5 m)	Cable with connector to piezo drive on one side and 3-pin Jaeger connector on the other side (length 1.5 m)	Cable with connector to scan stage on one side and 8-pin Jaeger connector on the other side (length 1.1 m)	Cable with 4 mm connectors on one side and 25-pin Jaeger connector on the other side (length 1 m)
Outside glove box	Cable with connector to SCV470 in one side and 8 pins LEMO connector in the other side (length 1 m)	Cable with connector to SCV470 on one side and 6-pin Jaeger connector on the other side (length 1 m)	Cable with connector to SCV470 on one side and 3-pin Jaeger connector on the other side (length 1 m)	Cable with connector to SCV470 on one side and 8-pin Jaeger connector on the other side (length 1.1 m)	Cable with connector to SCV470 on one side and 25-pin Jaeger connector on the other side (length 1 m)
Requirement					
Hole to make in the glove box/mm	12.1	21	21	27	45
Max. Required	1	1	1	3	2
Catalog n°	U-HC470ELE-L	U-HC470PSG	U-HC470PD	U-HC470STG	U-HC3300CL

*When used with an M470 and SP-300 configuration the SP-300 Ultra Low Current (ULC) glove box cable sets are also required.

USB-PIO

The USB-PIO, designed for use with the M470, allows external devices to be switched on and read. It can be used to control up to four different channels individually or collectively using the M470 software.

The USB-PIO can interface directly to user supplied cables, or to the supplied breakout PCB using the DB25 pin female connector.



USB-PIO specifications

	Information
PC Interface	USB
Power supply	5 V DC sourced via USB connection
Input / Output Interface	DB25 pin female connector
Input 1, 2, 3, 4	+24v DC @ 0.9mA Max (reverse voltage protected)
Output 1, 2, 3, 4	Common, Normally-Open and Normally-Closed relays, rated at +/-24v AC/DC @ 300mA resistive load Max

Complete control and analysis tools



The M470 software supports all the available techniques and uses a standard experiment model. The optional 3DIsoPlot™ and MIRA software provide extended analysis and imaging features. The software automatically recognises the installed techniques and seamlessly incorporates any experiment specific parameters.

The instrument is configured for area and line experiments and incorporates standard dc and ac techniques. It also allows the user to easily define, visualise, record and configure all experiment parameters as well as analyse and manipulate data post-experiment.

M470


The M470 software includes:

- SECM automated approach curve, with user-definable approach curve step size change and termination
- Higher resolution readout
- Manual or automatic tuning of the demodulation phase used in SVP and SKP
- Area map post processing including tilt correction, X or Y curve subtraction and 2D and 3D FFT
- Auto-sequencing of experiments, probe movement and area mapping
- Graphical Experiment Sequencing Engine (GESE)
- Support for multi-zone scanning
- Multiple data views for all experiments
- Peak analysis



3DIsoPlot™

3DIsoPlot™ features a user friendly interface and is ideal for displaying 3D maps of data produced by our range of scanning probe electrochemistry systems. 3DIsoPlot™ is suitable for displaying a wide range of data types from scanned to mathematical modelling data. 3DIsoPlot™ produces 3D plots in the form of shaded surfaces. Wire frame plots and colour contour maps of the surface are also available.



MIRA


MIRA (Microscopic Image Rapid Analysis) is an extremely powerful tool for the representation and analysis of data obtained by any scanning probe microscopy technique. It features an extensive range of 2D and 3D data representation tools for area scan data obtained with SECM. The package also has the ability to fit approach curve data using a wide range of equations which correspond to the conditions of the approach curve: with or without current offset, approach to a conductor or an insulator, generation/collection mode, etc. Such fitting gives access to parameters such as the actual probe to sample distance, the RG factor, the tip current in semi-infinite condition, the tip radius, amongst many others.

We serve our customers worldwide through our subsidiaries offices and our extensive distribution network.

Headquarters

BioLogic SAS

4, rue de Vaucanson
38 170 Seyssinet-Pariset
France
Phone: +33 476 98 68 31
Fax: +33 476 98 69 09



Subsidiaries offices

BioLogic USA, LLC

USA
Phone: +1 865 769 3800

BioLogic Science Instruments GmbH

Germany
Phone: +49 (0)551 38266900

BioLogic Science Instruments Ltd

United Kingdom
Phone: +44 (0) 333 012 4056

BioLogic Spain

Spain
Phone: +34 656 876773

BioLogic Pvt Ltd

India
Phone: +91 022 46055588

BioLogic Singapore

Singapore
Phone: +65 92335838

Brochure M470 released on May 2023, n°2

Always by your side. Wherever you are.

We here at BioLogic pride ourselves on the quality and robustness of our instruments. However if you, for whatever reason, encounter a problem with your instrument, our global support network will help find you a solution quickly and effectively.

If you need more information, or perhaps a little inspiration, you can browse our ever-growing support database with hundreds of Learning Center articles, application/technical notes and support videos at www.biologic.net.



Application notes



Learning center



Tutorials



Videos